

# R4U

# 350



## FLATHEAD

High quality general purpose resin thermal transfer ribbon. It performs well on virtually all criteria, like blackness, weather resistance, heat and steam. It can handle print speeds up to 200 mm/s (8 IPS) and can be used for the largest range of applications. R4U350 produces very dark black images with exceptional sharpness. Its anti-static backcoat extends the printhead life and maintains print quality.



### — Characteristics

- ✓ **Dark black images with exceptional sharpness**
- ✓ **Excellent scratch and smudge resistance**
- ✓ **Withstands high heat and steam**
- ✓ **Endures outdoor exposure, UV stable**

### — Substrates

Polypropylene (PP)  
Polyethylene (PE)  
PET / Polyester  
Nylon  
Polyimide  
Vinyl

### — Technical specifications

<b>PET film thickness</b>	4.5 µm
<b>Color</b>	Black
<b>Maximum print speed</b>	200 mm/s (8 ips)
<b>Ink melting point</b>	110°C (230°F)

#### **Storage**

Out of direct sunlight, storage between temperatures of 5°C to 35°C (41 to 95°F) in dry conditions

### — Applications

<b>Asset tags</b>	<b>Signage</b>
<b>Laboratories</b>	<b>Shelf labeling</b>
<b>Pharmaceutical</b>	<b>Horticulture</b>