Data sheet RT4U 920



Flathead Resin textile

RT4U920 is designed for printing care labels: nylon taffeta, polyester satin, polyester taffeta and acetate satin. With its improved sensitivity, it produces high-quality prints at lower energy levels which preserves the printhead.

It offers excellent resistance to washing, dry cleaning, chemicals and heat. Prints have high resistance to scratching and smudging.

Carrier

Color

Ink type

Characteristics

- + Smudge, scratch & abrasion resistance
- + Resistant to common chemicals
- + High-speed printing

Substrates

+ Coated paper Card paper

+

- + PET / polyester
- + Polypropylene (PP) + PVC
- + Polyethylene (PE)

Applications

- Industrial +
- Pharmaceutical
- Automotive +
- + Tyres
- + Packaging
- + Healthcare
- + Horticulture

Call us for more information:

Technical specifications

4.5µm

Black

Resin

+31(0)786427054

Storage: Out of direct sunlight. Storage between temperatures of 5 $^{\circ}$ C to 35 $^{\circ}$ C (41 to 95 $^{\circ}$ F) in dry conditions.

Printlabel BV | Bosch 133, 3353 GD Papendrecht, The Netherlands & +31 (0)78 642 7054 ☑ info@printlabel.nl

Printlabel